

KEPRO LIFTING CHAIN, GRADE 80

Material:	High Quality Alloy Steel
Quality Grade:	80
Surface Treatment:	Blackened
Safety Factor:	4 Times
Elongation:	10 to 14%
Hardness	38 - 42 HRC



TECHNICAL PARAMETERS

Chain Dia (mm)	Pitch (mm)	Dimensions (mm)			Weight / mtr. (Kgs.) ± 5%	Testing Details (in Tonnage)		
		Outside Width	Outside Length	Inside Width		Working Load Limit	Test Load	Breaking Load (min)
6	18	21	30	7.5	0.782	1.1	2.2	4.4
8	24	28	40	10	1.390	2.0	4.0	8.0
10	30	35	50	12.5	2.170	3.2	6.4	12.8
12	36	42	60	15	3.200	4.6	9.2	18.4
13	39	46.8	65	17.5	3.800	5.4	10.8	21.6
14	50	48	78	18	4.000	6.3	12.6	25.2
16	48	57.6	80	21.5	5.700	8.2	16.4	32.8
18	64	60	100	21	6.400	10.0	20.0	40.0
20	72	65	112	27	8.100	12.5	25.0	50.0
22	78	75	122	28	10.000	15.5	31.0	62.0
25	86	82	136	30	13.000	20.0	40.0	80.0
28	108	98	164	39	15.800	25.0	50.0	100.0
30	108	104	168	40	18.500	28.3	56.6	113.2
32	108	108	180	42	21.500	33.0	66.0	132.0

Due to progressive development of products, Kepro reserve the right to alter the specifications shown within this leaflet without notice.



Marketed By :

Kepro Tools & Equipments Pvt. Ltd.

www.kepro.in

