ROTA METER

The Rotameter is a simplest form of fluid measuring instrument. It consists of a borosilicate tapered glass tube placed vertically with its smaller diameter at the bottom. The float used in the tube is made up of heavier non-corrosive substance, which resists the vertical flow of the fluid passing through the annular space between the tube and the head of float. The fluid passing through the orifice, balances the weight of the float in the metered fluid and in equilibrium position, indicates the flow rate of the fluid against a calibrated external scale fitted by the side of the tube.



DESIGN FEATURES:

Range-ability 1:10

Construction type Side Plate.

Scale Detachable, direct reading.
Metering Tube Tapered, borosilicate.

Interchangeability Accepting with change of tube, floats and fluids.

Tube Sealing Gasket compressed from out side or '0' ring seal.

Piping Connection Rota table 360° without disturbing the Instrument.

Enclosures Weather and dust proof (IP-65 Type enclosures can also be provided on

request).

Glass Tube Length 400 mm

Scale Length 275 mm Approx

MATERIALS OF CONSTRUCTION:

Metering Tube Borosilicate Glass.

Float 316SS, Aluminum alloys, Teflon. Loaded Teflon, Hastalloy-C etc.

Contact Portion (Body) Stainless Steel as standard. Brass can be provided on request. (For

Threaded connection), M. S. Rubber lined and Teflon Lined.

Flanges M.S., C. S. with M. S. Spool, 316SS and 304SS with S. S. Spool also be

provided. with FLANGES

Side Plates M. S. epoxy Powder Coated

Optional Stainless Steel.

Packing Nitrile, Rubber, Viton or Teflon.

Float Stops Stainless Steel.

Safety Shielding Transparent clear Plastic / Glass at Front and Back.

Optional IP-65 Type enclosures.

Painting Necessary components are epoxy powder coated to prevent from

environmental corrosiveness.

ACCURACY

Accuracy of calibration for Standard Instruments is within \pm 2%. Where higher accuracies are required, special calibration techniques are used to obtain accuracies within \pm 1 %. Repeatability is excellent.



D. K. Instruments Pvt. Ltd.

An ISO 9001:2008 Certified Company

76/2, Selimpur Road, Dhakuria, Kolkata - 700 031.

Ph. No.: 91-33-2415 1310 / 2405 0944, Fax: 91-33-2415 2311.

E-mail: info@dkinstruments.com, Web Site: www.dkinstruments.com

Marketed By: